

# MATERIAL SAFETY DATA SHEET

FlashChrome Clear Coat

## Section 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** FlashChrome Clear Coat  
**Product Number:** CC  
**Product Use:** Coating.  
**Manufacturer/Supplier:** Fashion Paint USA  
3651 Lindell Road, Suite D 245  
Las Vegas NV  
89103  
**Phone Number:** 702-387-7200  
**Emergency Phone:** 702-387-7200  
**Date of Preparation:** December 10, 2009

## Section 2: HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

CAUTION

FLAMMABLE. HARMFUL BY INHALATION. HARMFUL IF SWALLOWED. IRRITATING TO EYES. IRRITATING TO SKIN.

**Potential Health Effects:** See Section 11 for more information.

**Likely Routes of Exposure:** Skin contact, eye contact, inhalation, and ingestion.

**Eye:** Irritating to eyes.

**Skin:** Irritating to skin.

**Ingestion:** Harmful if swallowed. May cause stomach distress, nausea or vomiting. Harmful: may cause lung damage if swallowed.

**Inhalation:** Harmful by inhalation. May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis.

**Chronic Effects:** Prolonged or repeated contact may dry skin and cause irritation.

**Signs and Symptoms:** Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Abdominal pain. Burning sensation. May cause burning of mouth, throat, and esophagus. Irritating to respiratory tract. Vapours may cause drowsiness and dizziness.

**Medical Conditions Aggravated By Exposure:** Because of its irritating properties, product may aggravate preexisting skin, eye, and respiratory conditions.

**Target Organs:** Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Potential Environmental Effects:** May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

# MATERIAL SAFETY DATA SHEET

FlashChrome Clear Coat

## Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Xylene	1330-20-7	15-40
Ethylbenzene	100-41-4	1-5
Methyl ethyl ketone	78-93-3	7-13
n-Butyl acetate	123-86-4	10-30
Isobutyl acetate	110-19-0	1-5

## Section 4: FIRST AID MEASURES

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

**Skin Contact:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

**Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

**General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

**Note to Physicians:** Symptoms may not appear immediately.

## Section 5: FIRE FIGHTING MEASURES

**Flammability:** Flammable by WHMIS/OSHA criteria.

**Means of Extinction:**

**Suitable Extinguishing Media:** Powder, foam, carbon dioxide. DO NOT USE WATER.

**Unsuitable Extinguishing Media:** Not available.

**Products of Combustion:** May include, and are not limited to: oxides of carbon.

**Explosion Data:**

**Sensitivity to Mechanical Impact:** Not available.

**Sensitivity to Static Discharge:** Not available.

**Protection of Firefighters:** Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## Section 6: ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

**Environmental Precautions:** Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

**Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

# MATERIAL SAFETY DATA SHEET

FlashChrome Clear Coat

**Methods for Clean-Up:** Soak into absorbent material. Spills of this material are a slipping hazard. Thoroughly wash the area with water after a spill or leak. Allow gas to dissipate harmlessly into the atmosphere.

**Other Information:** Not available.

## Section 7: HANDLING AND STORAGE

### Handling:

Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

### Storage:

Keep out of the reach of children. Keep container tightly closed. Do not store at temperatures above 49 °C / 120 °F. Keep away from food, drink and animal feedingstuffs.

## Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Xylene	100 ppm	100 ppm
Ethylbenzene	100 ppm	100 ppm
Methyl ethyl ketone	200 ppm	200 ppm
n-Butyl acetate	150 ppm	150 ppm
Isobutyl acetate	700 mg/m <sup>3</sup>	700 mg/m <sup>3</sup>

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

### Personal Protective Equipment:

**Eye/Face Protection:** Wear eye/face protection.

**Hand Protection:** Wear suitable gloves.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment.

**General Hygiene Considerations:** Handle according to established industrial hygiene and safety practices.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Not available.
<b>Color:</b>	Not available.
<b>Odour:</b>	Not available.
<b>Odour Threshold:</b>	Not available.
<b>Physical State:</b>	Liquid.
<b>pH:</b>	Not available.
<b>Viscosity:</b>	Not available.
<b>Freezing Point:</b>	Not available.
<b>Boiling Point:</b>	Not available.

# MATERIAL SAFETY DATA SHEET

FlashChrome Clear Coat

<b>Flash Point:</b>	< 21 °C (< 69.8 °F)
<b>Evaporation Rate:</b>	Not available.
<b>Lower Flammability Limit:</b>	Not available.
<b>Upper Flammability Limit:</b>	Not available.
<b>Vapor Pressure:</b>	Not available.
<b>Vapor Density:</b>	Not available.
<b>Specific Gravity:</b>	Not available.
<b>Solubility in Water:</b>	Not available.
<b>Coefficient of Water/Oil Distribution:</b>	Not available.
<b>Auto-ignition Temperature:</b>	Not available.
<b>Percent Volatile, wt. %:</b>	Not available.
<b>VOC content, wt. %:</b>	Not available.

## Section 10: STABILITY AND REACTIVITY

**Stability:** Stable under normal storage conditions. Keep in a cool place.

**Conditions of Reactivity:** Heat. Incompatible materials.

**Incompatible Materials:** Oxidizers. Light Metals.

**Hazardous Decomposition Products:** May include, and are not limited to: oxides of carbon.

**Possibility of Hazardous Reactions:** No dangerous reaction known under conditions of normal use.

## Section 11: TOXICOLOGY INFORMATION

### EFFECTS OF ACUTE EXPOSURE

#### Component Analysis

<b>Ingredient</b>	<b>LD<sub>50</sub> (oral)</b>	<b>LC<sub>50</sub></b>
Xylene	3523 mg/kg, rat	5000 ppm 4 hrs, rat
Ethylbenzene	3500 mg/kg, rat	Not available.
Methyl ethyl ketone	2737 mg/kg, rat	23500 mg/m <sup>3</sup> 8hrs, rat
n-Butyl acetate	10768 mg/kg, rat	2000 mg/m <sup>3</sup> 4hrs, rat
Isobutyl acetate	13400 mg/kg, rat	Not available.

**Eye:** Irritating to eyes. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

**Skin:** Irritating to skin. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

**Ingestion:** Harmful if swallowed. May cause stomach distress, nausea or vomiting. Harmful: may cause lung damage if swallowed. Abdominal pain. Burning sensation. May cause burning of mouth, throat, and esophagus.

**Inhalation:** Harmful by inhalation. May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis. Irritating to respiratory tract. Vapours may cause drowsiness and dizziness.

# MATERIAL SAFETY DATA SHEET

FlashChrome Clear Coat

## EFFECTS OF CHRONIC EXPOSURE

**Target Organs:** Not available.

**Chronic Effects:** Not hazardous by WHMIS/OSHA criteria.

**Carcinogenicity:** Hazardous by WHMIS/OSHA criteria.

### Ingredient

### Chemical Listed as Carcinogen or Potential Carcinogen \*

Xylene	Not listed.
Ethylbenzene	G-A3, I-2B, CP65
Methyl ethyl ketone	Not listed.
n-Butyl acetate	Not listed.
Isobutyl acetate	Not listed.

\* See Section 15 for more information.

**Mutagenicity:** Not hazardous by WHMIS/OSHA criteria.

**Reproductive Effects:** Not hazardous by WHMIS/OSHA criteria.

### Developmental Effects:

**Teratogenicity:** Hazardous by WHMIS/OSHA criteria.

**Embryotoxicity:** Hazardous by WHMIS/OSHA criteria.

**Respiratory Sensitization:** Not hazardous by WHMIS/OSHA criteria.

**Skin Sensitization:** Not hazardous by WHMIS/OSHA criteria.

**Toxicologically Synergistic Materials:** Not available.

## Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity:** May cause long-term adverse effects in the aquatic environment.

**Persistence / Degradability:** Not available.

**Bioaccumulation / Accumulation:** Not available.

**Mobility in Environment:** Not available.

## Section 13: DISPOSAL CONSIDERATIONS

### Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

## Section 14: TRANSPORTATION INFORMATION

### DOT Classification

UN1263, PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound) (vapor pressure at 50°C (122°F) not more than 110kPa), Class 3, Packing Group II

### TDG Classification

UN1263, PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound) (vapor pressure at 50°C (122°F) not more than 110kPa), Class 3, Packing Group II

# MATERIAL SAFETY DATA SHEET

FlashChrome Clear Coat

## Section 15: REGULATORY INFORMATION

### Federal Regulations

**Canadian:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**US:** MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

### SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Xylene	Not listed.	Not listed.	100	313
Ethylbenzene	Not listed.	Not listed.	1,000	313
Methyl ethyl ketone	Not listed.	Not listed.	5,000	313
n-Butyl acetate	Not listed.	Not listed.	5,000	Not listed.
Isobutyl acetate	Not listed.	Not listed.	5,000	Not listed.

### State Regulations

#### California Proposition 65:

This product contains a chemical known to the state of California to cause cancer.

### Global Inventories

Ingredient	Canada DSL/NDL	USA TSCA
Xylene	DSL	Yes.
Ethylbenzene	DSL	Yes.
Methyl ethyl ketone	DSL	Yes.
n-Butyl acetate	DSL	Yes.
Isobutyl acetate	DSL	Yes.

### HMIS - Hazardous Materials Identification System

Health - 2

Flammability - 2

Physical Hazard - 0

PPE - B

### NFPA - National Fire Protection Association:

Health - 2

Fire - 2

Reactivity - 0

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

### WHMIS Classification(s):

Class B2 - Flammable Liquid

Class D2A - Carcinogenicity

Class D2A - Teratogenicity and Embryotoxicity

Class D2B - Skin/Eye Irritant

### WHMIS Hazard Symbols:



# MATERIAL SAFETY DATA SHEET

FlashChrome Clear Coat

## SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

**OSHA (O)** Occupational Safety and Health Administration.

**ACGIH (G)** American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

**IARC (I)** International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

**NTP (N)** National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

## Section 16: OTHER INFORMATION

### Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

**Expiry Date:** December 10, 2012

**Version #:** 1.0

**Prepared by:** Nexreg Compliance Inc.

Phone: (519) 488-5126

[www.nexreg.com](http://www.nexreg.com)